


torque master[®]

ISO 9001:2015 Certified

Pure Innovation With Real Products!




Blow Molded Carrying Case



Standard Packing Box

There is a gamut of products ranging from Industrial Torque Wrenches, Torque Multipliers to Torque Screw Drivers which are created by a team of experts. It is our mission to provide the best of quality. To accomplish our mission, we have state of the art machinery and latest technology. We have been able to clinch such a huge number of clients because of the quality products and services being offered to them. Our clients are spread all over the world. The excellence in the quality and wide range of products differentiates us from others.

**Torque Wrench Price List
W.E.F 1st January 2022**



Torque wrench is now a must have tool for all garages and workshops. A torque wrench allows a user to precisely tighten a nut or a bolt to an optimum rotational force or torque.

Advantages of **torque master**[®] torque wrenches:

- **Extra Heavy Duty:** With the use of **high strength alloy steel** and precise heat treatment, the torque wrenches are built to last.
 - **Sturdy Storage:** Supplied with an aesthetically pleasing rugged blow moulded case (Up to TM 750/750R) and with a sturdy steel case (above TM 750/R) for extra care and protection for your valuable tool.
 - **Accuracy:** With a torque tolerance of $\pm 3\%$, the accuracy exceeds any national or international torque standard including ISO 6789: 2017.
 - **Three phase mechanism:** Sight, Touch and sound signal unmistakably lets the user know that the torque has been achieved even in a noisy environment.
 - **Comfort:** The synthetic double moulded handle is manufactured by specially selected resin (Up to TM 250/TM 250R) which provides comfort and durability and resists chemicals in automotive and industrial usage. The new Ergonomic shape and higher proportion of soft feel high grip material make it a lot more comfortable.
 - **Bi-Directional torque:** Torque can be applied in both right handed and left handed threaded nuts and bolts.
 - **Range:** Covers a vast range from 2 Nm to 3450 Nm.
 - **Ideal for confined spaces:** With the low re-engagement angle of 6 degrees for all ratchet type models, Working in confined spaces is not a hassle anymore.
 - **Available in** both Standard and Ratcheting type. Production type and open end type can be supplied against specific orders.
- During development, durability has been on top of our priority, both in terms of the **life of the tool** and the **calibration of the tool**. Full load **torture tests** are carried out on **each and every** torque wrench prior to dispatch. The result is a product that you can use with complete confidence that you have the best tool for the job.

Industrial Torque Wrenches Standard




Model	Square Drive	Range N.M	L.C	Range Lbf. Ft	L.C	Range Kgf.mts	L.C	Range Lbf.Ins	Head Width	Head Depth	Approx. OAL at min cap.	Weight (Kg)	Unit Price with Standard Packing Box (Prices in ₹)	Unit Price with Blow Molded Carrying Case (Prices in ₹)
TM 10	3/8"	2-14	0.5	2-10	0.5	0.2-1.4	0.1	20-120	23 mm	33 mm	310 mm	0.60	3,350.00	3,920.00
TM 25	3/8"	5-35	2	5-25	1	0.5-3.5	0.2	40-300	23 mm	33 mm	340 mm	0.70	3,590.00	4,160.00
TM 50	1/2"	10-70	2	8-50	2	1-7	0.2	100-600	28 mm	39 mm	450 mm	0.90	4,090.00	4,730.00
TM 100	1/2"	25-135	5	20-100	2	3-14	0.5	250-1200	28 mm	42 mm	550 mm	1.20	4,390.00	5,140.00
TM 160	1/2"	50-220	5	40-160	5	5-23	1	450-2000	32 mm	48 mm	610 mm	2.20	4,790.00	5,540.00
TM 160 Slim	1/2"	50-220	5	40-160	5	5-23	1	450-2000	28 mm	42 mm	595 mm	1.50	4,790.00	5,540.00
TM 250	1/2"	70-340	10	50-250	5	7-35	1	600-3000	32 mm	48 mm	770 mm	2.70	5,650.00	6,700.00
TM 300	3/4" 1/2"	80-400	10	60-300	5	8-40	1	720-3600	32 mm	55 mm	780 mm	2.80	6,890.00	7,940.00
TM 400	3/4"	135-540	15	100-400	10	14-56	1	N.A	48 mm	62 mm	1025 mm	6.50	10,600.00	14,400.00
TM 500	3/4"	135-675	15	100-500	10	14-70	2	N.A	48 mm	62 mm	1030 mm	6.60	11,250.00	15,050.00
TM 600	3/4"	200-815	15	150-600	10	20-84	2	N.A	48 mm	62 mm	1035 mm	6.90	12,350.00	16,150.00
TM 750	3/4"	255-1015	20	180-750	15	25-105	2	N.A	48 mm	62 mm	1120 mm	7.70	17,650.00	21,450.00
TM 750s	1"	255-1015	20	180-750	15	25-105	2	N.A	48 mm	67 mm	1120 mm	7.75	19,000.00	22,800.00
TM 1000	1"	540-1380	40	400-1000	20	55-140	5	N.A	56 mm	84 mm	1370 mm	13.80	21,900.00	N.A
TM 1400	1"	1000-1900	50	750-1400	25	105-195	5	N.A	70 mm	84 mm	1410 mm	15.50	30,500.00	N.A
TM 2000	1"	1350-2700	50	1000-2000	50	135-275	5	N.A	70 mm	84 mm	1550 mm	19.00	39,990.00	N.A
TM 2500	1"	1550-3450	50	1150-2500	50	160-350	5	N.A	70 mm	84 mm	1650 mm	22.00	44,990.00	N.A

Industrial Torque Wrenches Ratchet Type



Model	Square Drive	Range N.M	L. C	Range Lbf. Ft	L. C	Range Kgf.mts	L. C	Range Lbf.Ins	Swing Arc	Head Width	Head Depth	Approx. OAL at min cap.	Weight (Kg)	Unit Price with Standard Packing Box (Prices in ₹)	Unit Price with Blow Molded Carrying Case (Prices in ₹)
TM 10R	3/8"	2-14	0.5	2-10	0.5	0.2-1.4	0.1	20-120	06°	38 mm	39 mm	320 mm	0.60	3,690.00	4,260.00
TM 25R	3/8"	5-35	2	5-25	1	0.5-3.5	0.2	40-300	06°	38 mm	39 mm	350 mm	0.70	4,090.00	4,660.00
TM 50R	1/2"	10-70	2	8-50	2	1-7	0.2	100-600	06°	43 mm	42 mm	460 mm	0.90	4,790.00	5,430.00
TM 100R	1/2"	25-135	5	20-100	2	3-14	0.5	250-1200	06°	43 mm	48 mm	560 mm	1.20	5,590.00	6,340.00
TM 160R	1/2"	50-220	5	40-160	5	5-23	1	450-2000	06°	43 mm	48 mm	620 mm	2.20	5,790.00	6,540.00
TM 160R Slim	1/2"	50-220	5	40-160	5	5-23	1	450-2000	06°	43 mm	48 mm	605 mm	1.50	5,790.00	6,540.00
TM 250R	1/2"	70-340	10	50-250	5	7-35	1	600-3000	06°	43 mm	48 mm	780 mm	2.70	6,950.00	8,000.00
TM 300R	3/4" 1/2"	80-400	10	60-300	5	8-40	1	720-3600	06°	43 mm	55 mm	785 mm	2.80	7,950.00	9,000.00
TM 400R	3/4"	135-540	15	100-400	10	14-56	1	N.A	06°	67 mm	62 mm	1095 mm	7.30	12,200.00	16,000.00
TM 500R	3/4"	135-675	15	100-500	10	14-70	2	N.A	06°	67 mm	62 mm	1100 mm	7.40	13,250.00	17,050.00
TM 600R	3/4"	200-815	15	150-600	10	20-84	2	N.A	06°	67 mm	62 mm	1105 mm	7.50	14,200.00	18,000.00
TM 750R	3/4"	255-1015	20	180-750	15	25-105	2	N.A	06°	67 mm	62 mm	1200 mm	8.50	22,990.00	26,790.00
TM 750sR	1"	255-1015	20	180-750	15	25-105	2	N.A	06°	67 mm	67 mm	1200 mm	8.55	23,990.00	27,790.00
TM 1000R	1"	540-1380	40	400-1000	20	55-140	5	N.A	06°	95 mm	84 mm	1470 mm	17.50	25,990.00	N.A
TM 1400R	1"	1000-1900	50	750-1400	25	105-195	5	N.A	06°	95 mm	84 mm	1510 mm	18.80	33,590.00	N.A
TM 2000R	1"	1350-2700	50	1000-2000	50	135-275	5	N.A	06°	95 mm	84 mm	1650 mm	21.00	45,900.00	N.A
TM 2500R	1"	1550-3450	50	1150-2500	50	160-350	5	N.A	06°	95 mm	84 mm	1750 mm	25.00	48,990.00	N.A



Interchangeable Head Torque Wrenches




Model	Spigot	Range N.M	L.C	Range Lbf. Ft	L.C	Range Kgf.mts	L.C	Range Lbf.Ins	Head Width	Approx. OAL at min cap.	Weight (Kg)	Unit Price with Standard Packing Box (Prices in ₹)
TM 10i	16mm	2-14	0.5	2-10	0.5	0.2-1.4	0.1	20-120	25 mm	340 mm	0.60	3,550.00
TM 25i	16mm	5-35	2	5-25	1	0.5-3.5	0.2	40-300	25 mm	370 mm	0.70	3,950.00
TM 50i	16mm	10-70	2	8-50	2	1-7	0.2	100-600	28 mm	480 mm	0.90	4,450.00
TM 100i	16mm	25-135	5	20-100	2	3-14	0.5	250-1200	28 mm	580 mm	1.20	4,950.00
TM 160i	16mm	50-220	5	40-160	5	5-23	1	450-2000	32 mm	640 mm	2.20	5,250.00
TM 160i Slim	16mm	50-220	5	40-160	5	5-23	1	450-2000	28 mm	635 mm	1.50	5,250.00
TM 250i	16mm	70-340	10	50-250	5	7-35	1	600-3000	32 mm	800 mm	2.70	6,250.00

Open End Fittings 16mm Spigot




Part Number	Description	Unit Price (Prices in ₹)
OJ16-8 to OJ16-19	A/F 8mm to 19mm	1,800.00
OJ16-20 to OJ16-26	A/F 20mm to 26mm	2,000.00
OJ16-27 to OJ16-32	A/F 27mm to 32mm	2,200.00
RH16-1i	Ratchet Head 3/8"	2,750.00
RH16-2i	Ratchet Head 1/2"	2,750.00
RH16-3i	Ratchet Head 3/4"	4,350.00





Light Weight Torque Wrenches



Model	Square Drive	Range N.M	Least Count	Range Lbf. Ft	Least Count	Head Width	Head Depth	Swing Arc	Weight (Kg)	Approx OAL at min capacity	Unit Price (Prices in ₹)
KT 100	1/2"	10-100	0.50	9.25-75.85	0.37	44 mm	42 mm	06°	1.10	400	4,500.00
KT 200	1/2"	40-200	1.00	33.3-151.7	0.74	44 mm	42 mm	06°	1.25	470	4,850.00
KT 300	1/2"	60-300	1.00	48.10-225.7	0.74	44 mm	42 mm	06°	1.40	550	5,250.00
KT 400	3/4"	80-400	1.00	62.90-299.7	0.74	48 mm	50 mm	06°	1.70	680	6,950.00



Model	Spigot	Range N.M	Least Count	Range Lbf. Ft	Least Count	Weight (Kg)	Approx OAL at min capacity	Unit Price (Prices in ₹)
KTi 100	16mm	10-100	0.50	9.25-75.85	0.37	0.95	350	3,900.00
KTi 200	16mm	40-200	1.00	33.3-151.7	0.74	1.10	430	4,100.00
KTi 300	16mm	60-300	1.00	48.10-225.7	0.74	1.25	510	4,350.00
KTi 400	16mm	80-400	1.00	62.90-299.7	0.74	1.50	630	6,150.00

Torque Screw Drivers



Model	Square Drive	Range N.M	Range Kgf.cm	Weight (Kg)	Unit Price (Prices in ₹)
TMSD 15	1/4"	0.1-1.5	1-15	0.350	5,250.00
TMSD 50	1/4"	1-5	10-50	0.410	5,450.00

Torque Multipliers



Model	Input Square Drive	Output Square Drive	Multiplication Factor	Max Capacity (Nm)	Recommended Torque wrench	Unit Price (Prices in ₹)
TM 1	1/2"	3/4"	5	1700	TM 250R	20,240.00
TM 2	1/2"	1"	5	1700	TM 250R	20,500.00
TM 5	3/4"	1"	5	2750	TM 400R	26,990.00
TM 5/25	1/2"	1"	25	2750	TM 100R	42,350.00
TM 6	3/4"	1.1/2"	5	3450	TM 500R	30,250.00
TM 6/25	1/2"	1.1/2"	25	3450	TM 100R	48,950.00
TM 7	3/4"	1.1/2"	5	6220	TM 1000R	52,500.00
TM 7/25	1/2"	1.1/2"	25	6220	TM 250R	75,950.00
TM 9/25	3/4"	1.1/2"	25	9680	TM 400R	1,59,500.00
TM 11/25	3/4"	2.1/2"	25	17340	TM 500R	1,98,900.00
TM 13/25	3/4"	2.1/2"	125	48450	TM 400R	3,25,000.00



CHAND COMPANY

4772, Hauz Qazi, Delhi-110006

Ph.:23218581, 23213236, 23216796 Fax: 23213420

E Mail: info@chandcompany.com, chandcompany65@yahoo.com

Visit us at: chandcompany.com

Bank Details

Bank : KOTAK MAHINDRA BANK

Account No. : 0311161803 | Account Name : CHAND COMPANY

IFSC CODE : KKBK0000213 | UPI ID: Chand4772@kotak